



The 06x is a phono preamplifier offering balanced and unbalanced inputs and outputs and very low distortion, high-bandwidth performance with all possible loading combinations. The 06x supports low- and medium-output moving-coil and moving-magnet cartridges.

- Latest variant of the 06 phono stage, featuring substantial active and passive component
- Balanced and unbalanced inputs and outputs
- Switchable loading and gain for use with all cartridge types
- Multiple paralleled input FETs for exceptionally low noise
- All FET voltage gain with bipolar cur
- No overall
- DC-coupled design
- Wide bandwidth regulated supply with AC EMI and RFI line filter
- Double-sided gold plated circuit
- All anodized
- 10 year warranty / 5 year transferrable
- Designed, manufactured and assembled in the USA

Frequency Response:	+/- .2dB of RIAA with subsonic rolloff @ 14Hz
Distortion:	<.01% from 20Hz to 20kHz @ 3V peak into 600Ω or higher shunted by 100pF
Gain:	Unbalanced Output: 37dB @ 1kHz Balanced Output: 46db @ 1kHz
Maximum Output:	12V peak
Noise:	>87dB referenced to 1V output
Input Capacitance:	100pF to 1000pF
Input Impedance:	22-47kΩ
Output Impedance:	75Ω non-reactive unbalanced
Crosstalk:	70dB @ 20kHz
Dimension:	18" W x 9.75" D x 2.5" H