

Antipodes S- series Specifications

	S30	S60	S40	S20
Cena v Eur s DPH	3 790	2 390	5 990	2 850
Direct Stream Ethernet Output	No	No	Yes	No
USB Audio 2.0 Output – PCM to 32 bit/768kHz – DoP to DSD256 – Native DSD to DSD512	Yes	No	Yes	No
S/PDIF Output on RCA & BNC – PCM to 24bit/192kHz – DoP to DSD64	No	No	No	Yes
Analog Output on RCA	Yes	No	No	No
AES3 Output on XLR – PCM to 24bit/192kHz – DoP to DSD64	No	No	No	Yes
I2S Output on HDMI – PCM to 32bit/384kHz – DoP to DSD256 – Native DSD to DSD512	No	No	No	Yes
User installable storage	1 Bay SSD Slide Up to 8TB	No	1 Internal Bay Up to 8TB	No

Hardware Modules	V5X	HSL50.1	V5.2H	R1i
AC Supply – 110-120VAC 60Hz – 220-240VAC 50Hz	SMPS 12v	SMPS 12v	Yes	SMPS 12v
Width	165mm or 6.5"	165mm or 6.5"	165mm or 6.5"	165mm or 6.5"
Depth	260mm or 10.2"	260mm or 10.2"	260mm or 10.2"	260mm or 10.2"
Height	70mm or 2.8"	70mm or 2.8"	70mm or 2.8"	70mm or 2.8"
Weight	2.6kg or 5.7lb	3.5kg or 7.7lb	2.6kg or 5.7lb	2.5kg or 5.5lb
2 Years Warranty Extendable to 3 Years with Registration	Yes	Yes	Yes	Yes