

RATED POWER

V3:

400 Watts x 2 into 8 Ohms

800 Watts x 2 into 4 Ohms

Class A ~8 Watts

V2:

250 Watts x 2 into 8 Ohms

500 Watts x 2 into 4 Ohms

Class A ~12 Watts

V1:

150 Watts x 2 into 8 Ohms

300 Watts x 2 into 4 Ohms

Class A ~18 Watts

BANDWIDTH

DC or -3dB at 5 Hz through 100kHz depending on input

DISTORTION

Less than .03% from 10Hz to 20kHz at 350 Watts both channels driven into 4 through 8 Ohms

GAIN

26dB

CURRENT CAPABILITY

150 Amperes peak

SLEW RATE

50 Volts/microsecond

INPUT IMPEDANCE

50k Ohms unbalanced/10k Ohms balanced

OUTPUT IMPEDANCE

.04 Ohms from 20Hz to 20kHz

NOISE

More than -116dB referenced to rated output

POWER SUPPLY

3.0kVA toroidal transformer with independent rectifiers and 80,000 uF of capacitance

DIMENSIONS

Faceplate: 17 inches wide by 5.5 inches tall

Chassis: 16.75 inches wide by 6 inches tall by 14 inches deep

WEIGHT

62 lbs